

KIC Compakt

No compromises in beverage cooling!

The premium class among the KÜHLA cooling equipment. KIC Compakt has an advanced design and technology and comes with a variety of features. In the standard design, lockable doors and drawers are included. Front, inner area, machine compartment, sink base and corpus frame are completely manufactured in stainless steel 1.4301 (V2a), while the outer corpus is made of galvanised steel sheet. Front and inner area also available in stainless steel 1.4571 (V4a) for more robust uses.

Also available as ready-to-plug-in standard model or tailored individually to customer specifications.

Right: Exemplary design with a sink, worktop made of solid surface material and three cooling compartments, one with a revolving door (insulated glass front) to the left and two cooling compartments, each with two sliding drawers, partition above and below, each 1/2.



Worktop

- Worktop with 1–2 welded sinks (300 mm x 500 mm x 300 mm; including standpipe, 1 1/2" valve and drain fittings)
- Drip trough, seamless deep-drawn, with convex perforated metal sheet insert, with integrated glass rinser if required
- Surface in stainless steel 1.4301 (V2a) (solid surface material on request)

Cooling technology

- Cooling technology with Danfoss unit (fig. 1)
- R134a Cooling fluid
- Convection evaporator with expansion valve (fig. 2)
- $-\, {\rm Automatic} \; {\rm condensate} \; {\rm evaporation} \;$

Sink base

- Sink base made of stainless steel 1.4301 (V2a)
- With 2 sinks, waste tipper is also available

Corpus

- Corpus frame, front, inner area, machine compartment and sink base made of stainless steel 1.4301 (V2a)
- Optionally 2, 3 or 4 cooling compartments
- Easy-to-replace sponge rubber sealings in the corpus frame, in the doors and slides
- $-\mbox{\footnote{-}}$ Corpus floor with slope to the deep-drawn drain including drain fittings
- Corpus seamless and CFC-free, compression-moulded
- Fixed base with stainless steel panel
- Available in two series (890 mm & 790 mm corpus height)

Thermostat

 Easy-to-operate control unit with digital temperature display and On-/ Off-switch (fig. 3)

Sliding drawers/full lenght drawers

- Sliding drawers (fig. 4)/full lenght drawers made of stainless steel
 1.4301 (V2a) (drawer panels optionally with insulated glass-front and LED interior lighting)
- Handle bar (handle rail upon request)
- Lockable front panels
- PVC dividers
- Inner dimensions of the box: (W 407 mm x L 512 mm x H 150 mm)

Standard useable heights series 890/790 mm:

- Above 1/2, below 1/2 (above: 351/303 mm, below: 365/315 mm)
- Above 1/3, below 2/3 (above: 303/253 mm, below: 415/365 mm)
- Above 1/3, centre 1/3, below 1/3 (above: 213/182 mm, centre: 230/200 mm, below: 230/195 mm)

Revolving doors

- Lockable front panels made of stainless steel 1.4301 (V2a)
- Edge closure (handle rail upon request)
- Standard design with revolving doors in stainless steel 1.4301 (V2a), attached on the right and left side, with adjustable grating shelf or drum rack (revolving doors optionally with insulated glass-front and LED interior lighting)

Powder-coated front panels

Standard design in stainless steel 1.4301 (V2a). Powder-coated front panels in numerous colours upon request (fig. 5), as per RAL colour specifications, front panels also available with wooden décor.









